

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

SECTION 1. IDENTIFICATION

Product name : GASOLINE - ETHANOL

Product code : 12034, 11378, 11377, 12048, 12116, 12023, 11582, 11013, 11008, 11006, 11005, 11004, 11003, 11002, 11001, 10471, 10470, 10461, 10448, 10447, 10446, 10443

Other means of identification : SuperClean, SuperClean 94 (Montreal), Gasohol, Regular, Mid-Grade, Plus, RegularClean, PlusClean, marked or dyed gasoline Super, Pre Super, Premium (94 RO), E-10, Ultra 94, Ethanol blended gasoline, P10, E-15, P15

Manufacturer or supplier's details

Company name of supplier : Petro-Canada
Address : P.O. Box 2844, 150 - 6th Avenue South-West
Calgary, Alberta T2P 3E3
Canada, Telephone: 1-866-786-2671

Emergency telephone : CHEMTREC: 1-800-424-9300 (toll free) or +1 703-527-3887;
^CR^Suncor Energy: +1 403-296-3000

Recommended use of the chemical and restrictions on use

Recommended use : Gasoline-Ethanol is used in spark ignition engines including motor vehicles, farm vehicles, inboard and outboard boat engines, small engines and recreational vehicles.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 1

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure

Specific target organ toxicity : Category 1 (hematopoietic system)
- repeated exposure (Inhala-

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

tion)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H224 Extremely flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs (hematopoietic system) through prolonged or repeated exposure if inhaled.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | Common Name/Synonym | CAS-No. | Concentration (% w/w) |
|---|---|------------|-----------------------|
| Gasoline; Low boiling point naphtha - unspecified | Gasoline; Low boiling point naphtha - unspecified | 86290-81-5 | 70 - 97 |
| toluene | toluene | 108-88-3 | <= 60 |
| ethanol | ethanol | 64-17-5 | 3 - 15 |
| benzene | benzene | 71-43-2 | 0.05 - 1.5 |

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.
Artificial respiration and/or oxygen may be necessary.
Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Wash skin thoroughly with soap and water or use recognized

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

- skin cleanser.
Wash contaminated clothing before reuse.
Seek medical advice.
- In case of eye contact : Remove contact lenses.
Rinse immediately with plenty of lukewarm water, also under the eyelids, for at least 15 minutes.
Obtain medical attention.
- If swallowed : Rinse mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Never give anything by mouth to an unconscious person.
Seek medical advice.
- Most important symptoms and effects, both acute and delayed : Respiratory, skin and eye irritation; nausea; cancer.
- An indication of immediate medical attention and special treatment needed, if necessary : Treat symptomatically.
Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Dry chemical
Carbon dioxide (CO₂)
Alcohol-resistant foam
Water spray
Water fog.
- Unsuitable extinguishing media : Do NOT use water jet.
- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
- Hazardous combustion products : Carbon oxides (CO, CO₂), nitrogen oxides (NO_x), polynuclear aromatic hydrocarbons, phenols, aldehydes, ketones, smoke and irritating vapours as products of incomplete combustion.
- Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus and full protective wear.
Wear a positive-pressure supplied-air respirator with full face-piece.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : For personal protection see section 8.
Ensure adequate ventilation.
Evacuate personnel to safe areas.
Material can create slippery conditions.

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.
Remove all sources of ignition.
Soak up with inert absorbent material.
Non-sparking tools should be used.
Ensure adequate ventilation.
Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Do not ingest.
Avoid contact with skin, eyes and clothing.
Use only with adequate ventilation.
Keep away from heat and sources of ignition.
Keep container closed when not in use.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid inhalation of vapor or mist.
Use explosion-proof equipment.
Ensure all equipment is electrically grounded before beginning transfer operations.

Conditions for safe storage : Store in original container.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a dry, cool and well-ventilated place.
Keep in properly labeled containers.
To maintain product quality, do not store in heat or direct sunlight.
Ensure the storage containers are grounded/bonded.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|-------------------------------|--|-----------|
| Gasoline; Low boiling point naphtha -unspecified | 86290-81-5 | TWA | 300 ppm | CA AB OEL |
| | | STEL | 500 ppm | CA AB OEL |
| | | TWA | 300 ppm | CA BC OEL |
| | | STEL | 500 ppm | CA BC OEL |
| | | TWA | 300 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| toluene | 108-88-3 | TWA | 20 ppm | CA BC OEL |

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

| | | | | |
|---------|---------|-------|-----------|-----------|
| | | TWAEV | 20 ppm | CA QC OEL |
| | | TWA | 50 ppm | CA AB OEL |
| | | TWA | 20 ppm | ACGIH |
| ethanol | 64-17-5 | STEL | 1,000 ppm | CA BC OEL |
| | | STEV | 1,000 ppm | CA QC OEL |
| | | TWA | 300 ppm | CA AB OEL |
| | | STEL | 500 ppm | CA AB OEL |
| | | STEL | 1,000 ppm | ACGIH |
| benzene | 71-43-2 | TWA | 0.5 ppm | CA BC OEL |
| | | STEL | 2.5 ppm | CA BC OEL |
| | | TWA | 0.5 ppm | CA ON OEL |
| | | STEL | 2.5 ppm | CA ON OEL |
| | | TWAEV | 0.5 ppm | CA QC OEL |
| | | STEV | 2.5 ppm | CA QC OEL |
| | | TWA | 0.5 ppm | CA AB OEL |
| | | STEL | 2.5 ppm | CA AB OEL |
| | | TWA | 0.02 ppm | ACGIH |
| | | STEL | 0.1 ppm | ACGIH |

Engineering measures : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.
Use only in well-ventilated areas.
Use explosion-proof ventilation equipment.
Ensure that eyewash station and safety shower are proximal to the work-station location.

Personal protective equipment

Respiratory protection : Concentration in air determines protection needed.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Filter type : A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Hand protection
Material : polyvinyl alcohol (PVA), Viton(R). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

Remarks : Chemical-resistant, impervious gloves complying with an

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

| | |
|--------------------------|--|
| Eye protection | : approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. : Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded. Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Wear face-shield if splashing hazard is likely. Wear safety glasses with side shields to prevent eye contact. |
| Skin and body protection | : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. |
| Protective measures | : Wash contaminated clothing before re-use. |
| Hygiene measures | : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Physical state | : Clear liquid. |
| Color | : Clear to slightly yellow, undyed liquid. May be dyed for taxation purposes. |
| Odor | : Gasoline |
| pH | : No data available |
| Melting point and freezing point | : No data available |
| Boiling point, or initial boiling point and boiling range | : 26 - 225 °C |
| Flash point | : -43 °C Method: Cleveland open cup |
| Flammability | : Extremely flammable in presence of open flames and sparks. May accumulate static electrical charge. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. |
| Upper explosion limit / Upper flammability limit | : 7.60 %(V) |
| Lower explosion limit / Lower flammability limit | : 1.40 %(V) |
| Vapor pressure | : 307 - 802 mmHg (15 °C) |
| Relative vapor density | : 3 Air = 1 |

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

| | | |
|---|---|---|
| Relative density | : | No data available |
| Density | : | 0.7 - 0.78 kg/L (15 °C) |
| Solubility(ies) Water solubility | : | Hydrocarbon components slightly soluble in water., Ethanol is soluble in water. |
| Partition coefficient: n-octanol/water | : | No data available |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity Viscosity, kinematic | : | 0.6 cSt (40 °C) |
| Particle characteristics Particle size | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Reactivity | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | Hazardous polymerization does not occur. |
| Conditions to avoid | : | Extremes of temperature and direct sunlight. |
| Incompatible materials | : | Reactive with oxidising agents, acids and alkalis. |
| Hazardous decomposition products | : | May release COx, NOx, aldehydes, ketones, phenols, polynuclear aromatic hydrocarbons, smoke and irritating vapours when heated to decomposition. |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Ingestion
Inhalation
Skin contact

Acute toxicity

Harmful if inhaled.

Product:

| | | |
|---------------------------|---|---|
| Acute oral toxicity | : | Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method |
| Acute inhalation toxicity | : | Acute toxicity estimate: 18.33 mg/L Exposure time: 4 h Test atmosphere: vapor |

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Gasoline; Low boiling point naphtha -unspecified:

Acute oral toxicity : LD50 (Rat): 13,600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,750 mg/kg

toluene:

Acute oral toxicity : LD50 (Rat): 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): 12,125 mg/kg

ethanol:

Acute oral toxicity : LD50 (Rat): 7,060 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 32380 ppm
Exposure time: 4 h
Test atmosphere: vapor

benzene:

Acute oral toxicity : LD50 (Rat): 2,990 mg/kg

Acute inhalation toxicity : LC50 (Rat): 13700 ppm
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 8,240 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Based on available data, the classification criteria are not met.

Respiratory sensitization

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

Germ cell mutagenicity

May cause genetic defects.
May cause cancer.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Causes damage to organs (hematopoietic system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | | |
|------------------------|---|---|
| Waste from residues | : | The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labeled prior to recycling or disposal. Send to a licensed waste management company. Dispose of as hazardous waste in compliance with local and national regulations. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal. |
| Contaminated packaging | : | Contact local or business unit authorities for guidance on disposal of product. |

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3475
Proper shipping name : Ethanol and gasoline mixture
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Remarks : UN3475 if more than 10% ethanol. UN1203 if less than 10% ethanol.

IMDG-Code

UN number : UN 3475
Proper shipping name : ETHANOL AND GASOLINE MIXTURE
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes
Remarks : UN3475 if more than 10% ethanol. UN1203 if less than 10% ethanol.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3475
Proper shipping name : ETHANOL AND GASOLINE MIXTURE
Class : 3
Packing group : II
Labels : 3
ERG Code : 127
Marine pollutant : yes

Special precautions for user

Remarks : UN3475 if more than 10% ethanol. UN1203 if less than 10% ethanol.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

NPRI Components : toluene
ethanol
benzene
xylene

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified
naphthalene
1,2,4-trimethylbenzene

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

Canadian lists

No substances are subject to a Significant New Activity Notification.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL : Canada. British Columbia OEL
CA ON OEL : Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL : Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CA AB OEL / STEL : Short term exposure limit
CA AB OEL / TWA : Time weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit
CA ON OEL / TWA : Time-Weighted Average Limit (TWA)
CA ON OEL / STEL : Short-Term Exposure Limit (STEL)
CA QC OEL / TWA EV : Time-weighted average exposure value
CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Con-

SAFETY DATA SHEET

{ error: graphic
file not found:
E:\WWI\graphics

GASOLINE - ETHANOL

SDS Number: 000003000613

Version: 8.0

Revision Date: 2025/02/11

Print Date: 2025/02/12

centration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 2025/02/11

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN